



SUNTEC™

OIL PUMP TYPE T for Fuel oil #2 to #6 applications

This is a general specification leaflet ; for specific applications not covered herein, contact Suntec.

The SUNTEC T oil pump is specially designed for industrial heating applications using fuel oil #2 to #6 with high capacity. It is fitted with a preheater location to render cold starting easier.

APPLICATIONS

- Fuel oil #2 to #6 (for lighter oil and kerosene applications, contact SUNTEC), B6-B20 (blends from 6% up to 20% biodiesel, per ASTM D396).
- The use of a SUNTEC TV valve is recommended to regulate the pump pressure.

PUMP OPERATING PRINCIPLE

The gear set draws oil from the tank and transfers it to an external valve that regulates the oil pressure.

Bleed :

The plug of the pressure gauge port must be loosened until the air is evacuated from the system.

Note :

The bypass plug inserted between high pressure and shaft seal is only intended to change the pump rotation, check the presence of this plug with a 4 mm Allen key in the pressure outlet of the pump.

Caution : changing the direction of pump rotation involves changing all pump connections.

PREHEATING FACILITY

Care should be taken to avoid starting pump with high viscosity cold oil leading to pump and coupling damage. For this reason, the T pump body includes a cavity to accept an electric preheater. This cavity has been located to give maximum heat transfer from the heater to the oil in the pump without direct contact between the heater cartridge and the oil.

Heaters should be connected for a period of time prior to starting the pump. When the right temperature is reached, they can be switched off or left permanently switched on to maintain fluid oil in the pump during the periodic burner shut-downs.



The oil supply, pipes and filters must be separately heated.

T

T - US - Ed.4 - June 2019

PUMP IDENTIFICATION

*(Not all model combinations are available
Consult your Suntec representative)*



TECHNICAL DATA

General

Mounting	Flange mounting	
Connection threads	Cylindrical according to ISO 228/1	
Inlet and return	G 3/4	
Nozzle outlet	G 3/4	
Pressure gauge port	G 1/4	
Vacuum gauge port	G 1/4	
Shaft	Ø 20 mm	
Weight	17,2 lbs (T 2)	7,9 lbs (T 3)
	19,2 lbs (T 4)	20,7 lbs (T 5)



Choice of heater

Cartridge	Ø 12 mm
Fitting	according to EN 50262
Rating	80-100 W

Hydraulic data



Nozzle pressure range	@ 2,4 cSt	@75 cst
T 2/3/4:	max 350 psi max	max 580 psi max
T 5:	max 350 psi max	max 435 psi max
Operating viscosity**	2,4 - 75 mm²/s (cSt)	
<i>**:</i> Higher viscosity oil can be used by feeding the pump and by heating the oil to lower its viscosity under 75 cSt. For kerosene applications, contact SUNTEC		
Oil temperature	32 - 302°F in the pump	
Inlet pressure	6,5 psi max. vacuum to prevent air separation from oil Inlet feed pressure : 75 psi max.	
Rated speed	3600 rpm max.	
Torque (@ 40 rpm)	0.40 N.m	

Pump capacity



Data shown are for new pumps, with no allowance for wear.


Power consumption



PUMP DIMENSIONS

Example shows pump with "A" rotation - Reverse all pump connections for "C" rotation - Dimensions in mm.

	T2	T3	T4	T5
(mm)	68	73	78	87



We reserve the right to change specifications without prior notice.

T - US - Ed.4- June. 2019